



PATENT
Docket No.: ZAY-99-029 *H7B*
Affair
10/28/02

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Group Art Unit: 2182

Examiner: Park, I.

Serial No. 09/431,703

Filed: November 1, 1999

In re Application of: Steven W. Brown

For: METHOD AND APPARATUS FOR DYNAMIC LINK DRIVER
CONFIGURATION

COPY OF PAPERS
ORIGINALLY FILED

Certificate of Mailing

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as First Class Mail, in an envelope addressed to Director of Patents, Washington, D.C. 20231, on 8-6-02, Signed Tina Bounds
Tina Bounds

RESPONSE TO OFFICE ACTION RECEIVED

Director of Patents
Washington, D.C. 20231

AUG 16 2002

Technology Center 2100

Dear Sir:

The following is being submitted in response to the Office Action dated 4/08/02.

In the Specification

Please replace the paragraph beginning at page 6, line 4 with:

B1
The link devices for which the invention provides link driver configuration may comprise the same or different types. In cases where the link devices are the same type, the invention configures the link driver for each link device according to the behavior of the link device (e.g., the type of communication carried out by the link device) as well as the capabilities of the link device. For example, in a module having first and second nodes, each node having a link device, the first node may be configured for asynchronous communication, while the second node may be configured for isochronous communication. Even though the link device in the first node is identical to the link device in the second node, the invention may provide link driver configuration